

# Authentication settings for the SASL authentication type

Teamwork Administrator's Console

Menu

Properties

Secured Connection

Repository

LDAP Integration

Active Users

Projects

Log File

☒ Enable LDAP Integration

Test Connection

Authentication Settings

Authentication Type\* : SASL

Authentication Identity\* : \$(login)  
Example: \$(login)

Authorization Identity : \$(login)@NoMagic  
Example: \$(login)

Realm :

Mechanism :  
Example: DIGEST-MD5

☒ Auto-add unknown users if they login successfully

Refresh

Apply Changes

Exit

Teamwork Administrator's Console, LDAP Integration tab. Authentication Settings (SASL)

Authentication Settings are described in the following table.

Setting Name	Description
Authentication Identity	Login name supplied by the user is transformed to an authentication identity when authenticating. The authentication Identity is a mandatory template. The template recognizes a single keyword \$(login). An example of a template:  \$(login)
Authorization Identity	Login name supplied by the user is transformed to an authorization identity when authenticating if the Authorization Identity template is specified. The template recognizes a single keyword \$(login).  An example of a template:  \$(login)  or  \$(login)@example
Realm	Specifies the realm of an authentication identity for the SASL bind.

**Mechanism**

Specifies the SASL mechanism to be used for authentication. An example:

DIGEST-MD5