

UML to Equivalent OWL in OWL Functional Syntax

There are various syntaxes available for encoding OWL ontologies. The Concept Modeler can export UML to an OWL ontology using the following syntaxes:

- **RDF/XML**. It is the original standard syntax for writing RDF (Resource Description Framework), which is a general-purpose language for representing information on the Web. Although it is wordy and difficult to read, it is the only syntax written in various concrete formats called RDF serialization formats, and it is mandatory to be supported by OWL 2 tools. It provides an XML representation of an RDF graph. This syntax is the default syntax used in the Concept Modeler.
- **JSON-LD** or JavaScript Object Notation for Linked Data is a method of encoding linked data using JSON, which is a concrete RDF syntax. JSON-LD is used to map JSON terms (keys and values) to IRIs, giving them a global context. A JSON-LD document is both an RDF document and a JSON document and correspondingly represents an instance of an RDF data model.
- **OWL Functional**. It is a simple text-based syntax designed to be easier for specification purposes, and to provide a foundation for the implementation of OWL 2 tools such as APIs and reasoners. It is used in most of the OWL 2 specification documents as the primary presentation syntax that translates the structural specification into other concrete syntaxes. A functional-style syntax ontology document consists of sequences of Unicode characters and is encoded in UTF-8.
- **Turtle**. A concrete syntax for RDF, Turtle (Terse RDF Triple Language) is a plain-text RDF representation. It is more concise, and easier to read and edit manually than RDF/XML. A Turtle document is a collection of RDF-triples, which groups three URIs to make a triple and provides ways to abbreviate information, e.g., by factoring out common portions of URIs. Each triple has the format: <subject> <predicate> <object>. Each statement ends with a period, and each element in the triple is an URI, except the <object>, which can be a bit of text or a number.
- **Manchester**. It provides a compact textual-based representation of OWL ontologies that is easy to read and write. It uses IRIs as term identifiers. The syntax for entering and displaying annotations and descriptions in the Manchester OWL syntax closely corresponds to the syntax in the OWL Functional syntax. A Manchester OWL document consists of sequences of Unicode characters, and is encoded in UTF-8.

This section gives examples that show the transformation of UML modeled in the Concept Modeler to an exported OWL ontology. The OWL ontologies are presented in OWL Functional Syntax.



Note

- A model may contain elements, (e.g. classes, properties, or datatypes) that belong to other models. When exporting the model, the Concept

Modeler will include the OWL declaration of the elements that exist in the current model only, not those of the other models.

Related pages

- However, if the entity that belongs to another model is an object property with an inverse property defined, you will see the OWL declaration of
- [Setting the concept model export syntax](#)
- [Using the inverse property in the current OWL ontology upon export.](#)



Unknown macro: 'list-children'