

Values

The valid values that you can use in an expression are as follows

- Real Number
- Complex Number
- Boolean
- Matrix

Real Number

`x = 3.14159`

`y = 2`

Complex Number

`c = 3 + 4i`

`d = 1.25 + 0.25i`



Note

An 'i' character in an expression can be parsed as either an imaginary unit or a character of a variable name. If the character 'i' is placed after a number, and the next character is neither an alphabet nor number, it will be parsed as an imaginary unit. Otherwise, it will be parsed as a variable. The examples are as follows

- `ca = 1i 'i'` is parsed as an imaginary unit.
- `cb = i 'i'` is parsed as a variable.
- `cx = 3.25i 'i'` is parsed as an imaginary unit.
- `cy = 4i4 'i'` is parsed as the first character of a variable name 'i4'

Boolean

`a = true`

`b = false`

Matrix

`U = [1.0, 2.0, 3.0; 4.0, 5.0, 6.0; 7.0, 8.0, 9.0]`

`A = [true; false; false; true]`

You can add a matrix to the built-in Math Solver by using the following syntax (a semicolon is used as a row separator and comma or space is used as a comma separator). The examples are as follows

`U = [1.0, 2.0, 3.0; 4.0, 5.0, 6.0; 7.0, 8.0, 9.0]`

$$U = \begin{bmatrix} 1.0 & 2.0 & 3.0 \\ 4.0 & 5.0 & 6.0 \\ 7.0 & 8.0 & 9.0 \end{bmatrix}$$

`A = [true; false; false; true]`

$$A = \begin{bmatrix} \text{true} \\ \text{false} \\ \text{false} \\ \text{true} \end{bmatrix}$$

You can refer to a matrix element with the row and column index specified in round brackets after a matrix name. The examples are as follows (see U above)

`U(1, 1)` is 1.0

`U(2, 3)` is 6.0

You can also refer to a matrix element with only one index specified in round brackets after a matrix name. In this case, the matrix will be considered as a column-major order matrix. The elements on the given column-major order index will be returned. The examples are as follows (see U above)

U(2) is 4.0

U(6) is 8.0