Deploying the DOORS driver for IBM Rational DOORS

Before adding a DOORS Data Source, you must deploy the DOORS driver.



• Driver deployment copies the DXL script file into the DOORS addin folder and updates the registry for DOORS to recognize the addin path.

Therefore, you must run MagicDraw or Cameo products as an administrator to allow these operations during driver deployment.

• You must close the DOORS application before driver deployment since folders are write-protected when the application is active. To deploy the DOORS driver

1. From the MagicDraw[®] main menu, click Tools > DataHub > Driver Deployment. The Driver Deployment dialog opens.

Тоо	<mark>ls </mark> Analyze Collaborate	Window	Hel	р		
	Project Merge			eate I	Diagram	1
ABS	Report Wizard	Ctrl+Shift	+G			
	Check Spelling					
	Expression Evaluation					
	Generate Code		>			
	DataHub >			Synchroni	ize updates to Data Source	
	ParaMagic Plugin				DataHub I	Explorer
	•				DHLink Pa	anel
					Prepare D	ata For Module
					Clean Up	DataHub Database
					DHLink Su	ummary
					Schema N	/lap Manager
					Alias Man	iager
					Migrate D)ataHub
					Driver Dep	ployment
				۹,	Create OS	SLC Query
					Actions	>
					3rd Party	Libraries Info

2. From the Version drop-down list, choose a version of IBM® Rational® DOORS® that you would like to add.

Marning	
U wanning	Add
It is important to choose the DOORS version before you clicl	k

Driver Deployment	×
IBM Rational DOORS	*
Deployment parameters	
Version: 9.5 -	
C:\Program Files (x86)\IBM\Rational\DOORS\9.5	Add
	Remove
	Close

	Add	
	Auu	
3. Click		An Open dialog appears which prompts you to choose your DOORS installation directory. Locate it and then click Open .
		and and an an and de DODD Date Original
The DOG	JRS ariver is no	w deployed, and you can now add a DOORS Data Source.

Related page

• Driver deployment