Creating OSLC queries

There are two types of OSLC queries you can construct to query the DOORS® Next Generation artifacts repository - simple or basic query and advanced query based on SQL or SPARQL. You can find the details of OSLC queries and more examples of queries and their syntax on the OSLC Specification website.

To create and run a simple or basic OSLC query

1. Do one of the following

    ○ On the main menu, click **Tools** > **DataHub** > **Create OSLC Query** from MagicDraw®.

    ○ On the **DataHub Explorer** toolbar, click the **Create OSLC Query** button.

   The **OSLC Query Editor** dialog opens.

2. Fill out the information that you want to create the query to search for.

3. Click 〔 Run 〕. The results of the query, if any, appears below the *Type text to search* box.

✅ **Tip**

- You can filter the search results of the query by using the *Type text to search* box.
- You can click 〔 Save as alias 〕 to save the results in **Alias Manager**.

To create and run an advanced query

1. Do one of the following
   - On the main menu, click **Tools** > **DataHub** > **Create OSLC Query** from MagicDraw®.
   - On the **DataHub Explorer** toolbar, click the **Create OSLC Query** 🔍 button.

   The **OSLC Query Editor** dialog opens.

OSLC Query Editor

Basic Query | **Query Editor**

Data source: Requirements Management

Query Label:

Query String: `1 ric.com:9443/rm/views?oslc.query=true`

Run

Matched items: 829 result(s).

Operation: Create OSLC Link

Type text to search

- Query
  - 123
  - Back Office System
  - Back office administrator
  - Beneficiary
  - Charity Coordinator
  - Customer
  - Donor
  - Financial Business Manager
  - Image 0
  - Image 1
  - Image 2
  - Image 3
  - Registered User
  - logo_JK enterprises
  - Administration
  - Appendix A: Terminology/Glossary/Definitions list

New Query **Save as alias**

2. Click the **Query Editor** tab. In the **Query String** box, type your query using the simple or basic query language, e.g., *https://10.1.1.70:9443 /rm/views?oslc.query=true* or using the SPARQL query language, e.g., *https://host:port/bugs?oslc.select=dcterms:created,dcterms:creator{foaf: familyName}&oslc.where=cm:severity="high"*.

3. Click **Run**. The results of the query, if any, appears below the *Type text to search* box.

⊘ **Tip**

- You can filter the search results of the query by using the *Type text to search* box.
- You can click **Save as alias** to save the results in **Alias Manager**.