# **Using Simple Navigation**


## On this page

• Manipulations in Expert mode


Use the simple navigation operation type, if you need to specify a direct relation between the elements through model relationships, properties, or tags.

To specify a simple navigation as criteria

1. Click Simple Navigation on the left side of the dialog.



2. Select a relationship, property, or tag.




3. Specify other options described in the table below:

Column	Mode	Description
Relation Criterion	Standar d /Expert	Name of a relationship, property, or tag. The whole list is by default filtered and shows only these relationships, properties, and tags that are available for the Contextual element type. To see the full list, click to clear the check box below the list.
Is Applied	Standar d /Expert	Select the check box to define the appropriate relationship, property, or tag as criteria for the calculation. To clear all the selected criteria, click the Clear All button.
Direction	Standar d /Expert	Select from the drop-down list the direction of the appropriate relationship, property, or tag. A source is the Contextual element. A target is the result of the calculation.
		<ul> <li>• The Source To Target direction means that only the outgoing relations, which are pointing from the source element to the target element, will be treated as a result of this criterion.</li> <li>• The Target To Source direction means that only the incoming relations, which are pointing from the target element to the source element, will be treated as a result of this criterion.</li> <li>• If the Both direction is chosen, both above-described cases will be treated as a valid result.</li> </ul>
		If the direction is defined for properties or tags, then
		<ul> <li>The Source To Target direction means that only the properties, which exist in the source element, will be treated as a result of this criterion.</li> <li>The Target To Source direction means that only the properties, which exist in the target element, will be treated as a result of this criterion.</li> <li>If the Both direction is chosen, both above-described cases will be treated as a valid result.</li> </ul>

## Manipulations in Expert mode


The **Expert** mode allows for changing the Contextual element of a simple navigation criterion as well as creating a new operation, where the result of the simple navigation operation is used as an argument.



Column	Mode	Description
Properties		Click the button and in the open dialog specify the properties of the selected relationship.
Include Relationshi p Subtypes	Expert	Select the check box to include the subtypes of the selected relationship types.
Include Relationshi p Custom Types	Expert	Select the check box to include the custom relationship types that extend the selected relationship types.
Filter by Property Value	Expert	Click the button and in the open dialog select one or more properties of the selected relationship and specify their values for a more specific filter.
Result Type	Expert	Click the button and in the open <b>Select Element Type</b> dialog select one or more result element types. The Result Type column is available only in the <b>Query</b> and <b>Expression</b> dialogs. You can define the element types for representation on a Dependency Matrix and Generic table. Moreover, you can define the element types for representation on a Relation Map.
Style	Standar d /Expert	Click the button and in the open dialog select the color and style to represent the appropriate relationship, property, or tag. The column is available only in the <b>Relation Criterion</b> dialog.

To change the Contextual element of a simple navigation criterion

- 1. On the left side of the dialog, expand the simple navigation criterion and select the Context parameter.
- 2. On the Context specification panel, click the Reset button.




The value of the Context parameter becomes null.

3. Select a new context from the list of operations and element types.

Prestore the original context, expand the Other group and click Contextual Variable.

### Other



3. Specify other parameters of the new operation.

### Related pages

- Specifying criteria for querying model
  - Getting started with specifying criteria
  - Using Metachain Navigation

  - Using Find operationUsing Implied Relations
  - Creating new operations
    - Calling operations from the model
       Creating script operations