Automatic initialization of context and runtime objects

On this page

- Context initialization
- Runtime object initialization

Cameo Simulation Toolkit is capable of initializing both context and runtime objects automatically even if a simulation context does not exist, and no object is configured to initiate the runtime objects.

Context initialization

When executing a Behavior, Cameo Simulation Toolkit allows you to simulate its context as well.

To simulate a Behavior with its context

• Right-click a Behavior or a Behavior's diagram and select Simulation > Run with Context to execute it together with its context.



• Right-click a Behavior or a Behavior's diagram and select Simulation > Run to execute it without its context.



When you simulate a Behavior with its context, Cameo Simulation Toolkit will initialize the context of the selected Behavior and simulate the Classifier Behavior. During the Classifier Behavior simulation, if the runtime object of the context Classifier is stable, the selected Behavior will be simulated.

If a selected Behavior has no context, the Run with Context menu will be disabled.



Running a model simulation using the shortcut menu.

Runtime object initialization

When you use an **InstanceSpecification** to initialize a runtime object, you will also need to use the corresponding slot values of such **InstanceSpecificati on** to initialize the feature values of the runtime object. Cameo Simulation Toolkit will use the default value of the corresponding feature (property) of each slot if the slot value is empty.

The value of each feature (property) will be automatically initialized only if its **Lower-value Multiplicity** is more than zero or is undefined. Otherwise (the feature's **Lower-value Multiplicity** is zero), the feature value will be empty (nothing is initialized). However, characteristic of the initialization depends on the type of the feature. The following sections explain the types of feature that can influence initialization characteristics

Structural feature typed by primitive datatype

The default value of a structural feature, which is typed by a primitive datatype, is its initialized value. This default initialization value, which can be set from **Options > Project > Simulation** as shown in following figure. When true and value property has no default value, the value will be initialized to 0 value. The default value is **false**.

The datatypes which are affected by this option are listed in the table as follows

Project Options		×		
Specify general project properties Specify the validation, project dependency checker options and other general project-specific options.				
Q Type here to filter options	Simulation			
Image: Simulation Image: Simulation <t< th=""><th>1 Implement of the second second</th><th>☐ false JavaScript Rhino [on] fUML Engine [on] Interaction Engine [on] Parametrics Engine [on] SCXML Engine ☐ false ✓ true</th></t<>	1 Implement of the second	☐ false JavaScript Rhino [on] fUML Engine [on] Interaction Engine [on] Parametrics Engine [on] SCXML Engine ☐ false ✓ true		
	Treat All Objects as Active ✓ true Terminate Behavior on Exception Thrown ✓ true Initialize Empty Values to 0 ☐ false Initialize Empty Values to 0 ✓ When true and value property has no default value, the value will be initialized to 0 value. Reset to Defaults			
		OK Cancel Help		

The Simulation Project Options - Initialize Empty Values to 0.

This initialization value applies to numerical datatypes only. For other types, see the table for values used for automatic initialization of the Structural Feature typed by primitive datatype as follows.

Primitive DataType (QualifiedName)	Value
 UML Standard Profile::UML2 Metamodel:: PrimitiveTypes::Boolean PrimitiveValueTypes::Boolean (SysML Profile.mdzip) UML Standard Profile::MagicDraw Profile::datatypes::bo olean 	false

 UML Standard Profile::UML2 Metamodel:: PrimitiveTypes::Integer UML Standard Profile::UML2 Metamodel:: PrimitiveTypes::UnlimitedNatural PrimitiveValueTypes::Integer (SysML Profile.mdzip) PrimitiveValueTypes::UnlimitedNatural (SysML Profile. mdzip) UML Standard Profile::MagicDraw Profile::datatypes::Int UML Standard Profile::MagicDraw Profile::datatypes::Iong UML Standard Profile::MagicDraw Profile::datatypes::Iong UML Standard Profile::MagicDraw Profile::datatypes::Iong 	All numerical data types pick up their default initialization value from the Project Options as shown in the above figure.
 UML Standard Profile::UML2 Metamodel:: PrimitiveTypes::Real PrimitiveValueTypes::Real (SysML Profile.mdzip) UML Standard Profile::MagicDraw Profile::datatypes::do uble UML Standard Profile::MagicDraw Profile::datatypes::flo at 	All numerical data types pick up their default initialization value from the Project Options as shown in the above figure.
• Enumeration	UML Standard Profile::UML2 Metamodel::PrimitiveTypes::Real
 UML Standard Profile::UML2 Metamodel:: PrimitiveTypes::String PrimitiveValueTypes::String (SysML Profile.mdzip) 	"" (Empty String)

Structural feature typed by non-datatype

If the type of a structural feature is not a datatype, the conditions are applied as follows

- If the structural feature has a non-empty slot value, it will be initialized with such value.
- Otherwise, if the structural feature's default value is specified, it will be initialized with the default value.

If the structural feature also has internal feature(s), for each internal feature, the conditions are applied as follows

- If the internal feature has a non-empty slot value, it will be initialized with such value.
- Otherwise, if the internal feature's default value is specified, it will be initialized with the default value.

If an internal feature also has its own internal feature(s), the same rule above will be applied recursively.

Structural feature typed by user-defined eatatype

For a structural feature typed by a user-defined datatype, the conditions are applied as follows

- If the Datatype has internal structural feature(s), the value of the structural feature will be initialized as described in Structural feature typed by non-datatype.
- If the Datatype has no internal structural feature, the following conditions are applied
 - The value of the structural feature will be initialized as described in Structural feature typed by primitive datatype if the Datatype is inherited from a primitive datatype.
 - The initialized value of the structural feature will be its default value if the Datatype is not inherited from any primitive datatype. If the default value of the feature is, however, not specified, the initialized value will be empty.

Related pages

- Classifier Behavior property
- · Getting a structural feature value