

# General parameters

The following parameters are used with the authentication server to ensure proper working functionality.

Parameter	Description	Default value
authentication.token.expiry	The authentication ID token expiration time in seconds.	604800
authentication.code.token.expiry	The authentication code expiration time in seconds.	15
authentication.implicit.token.expiry	The authentication ID token expiration time in seconds for the implicit authentication flow (e.g., used for MagicDraw UML).	86400
authentication.unlimited.token.expiry	Authentication ID token that has extremely long expiration time and should only be used in server-server requests when there is a need to perform regular batch jobs.	630720000
authentication.client.ids	The valid client IDs, separated by commas.	MAGICDRAW, webApplicationPlatform, twcSynchronizationManager
authentication.client.implicit	The implicit authentication flow client IDs (separated by commas).	MAGICDRAW
authentication.client.unlimited	Client IDs that use token ID of unlimited expiration (separated by commas).	twcSynchronizationManager
authentication.redirect.uri.whitelist	A list of allowed redirect URIs. The authentication server client should pass a valid redirect URI to an authorized endpoint.	<a href="https://\${webapp.server.ip}:8443/">https://\${webapp.server.ip}:8443/</a> , <a href="https://\${twc.server.ip}:8111/">https://\${twc.server.ip}:8111/</a> , <a href="https://md_redirect/">https://md_redirect/</a>
authentication.disable.credentials	Ability to disable username/password authentication if external user authentication (CAC, SAML) is used.	false